DESCRIPTION

DATA STORAGE CIRCUIT, DATA WRITING METHOD IN THE SAME,
AND DATA STORAGE DEVICE

Technical Field

The present invention relates to a data storage circuit for storing predetermined data, a data writing method in the data storage circuit, and a data storage device.

Background Art

Conventionally, in electronic computers including a̶ personal computers, a data storage circuit composed of a combination of a large number of storage elements is provided in a semiconductor device such as a CPU and a memory IC. Data i̶s̶ are stored in the data storage circuit so as to execute various types of processing.

The storage elements in such a data storage circuit are normally configured so that 1-bit data is stored in each of the storage elements. More specifically, the storage element is capable of keeping two different states. When one state is represented by "0" and the other state by "1", data of "0" or "1" is stored by keeping any one of the states. A large number of such storage elements are provided to enable the storage of data in an amount corresponding to the number of provided storage elements.

Storage elements having a wide variety of structures are known as such storage elements. For example, a storage element of a flash memory, which

consists of an N-channel MOSFET (Metal Oxide Silicon Field Effect Transistor), is capable of storing data "0" and "1" while a state where charges are accumulated in a floating gate layer provided for a gate electrode section

5   is represented by "1" and a state where no charge is accumulated in the floating gate layer is represented by "0" or vice versa.

A storage element of an MRAM (Magnetic Random Access Memory), which consists of a ferromagnetic tunnel

10   junction element, is capable of storing data "0" and "1" while a state where a the direction of magnetization of a free magnetization layer is anti-parallel to that of a fixed magnetization layer is represented by "1" and a parallel state by "0" or vice versa.

15   In a data storage circuit provided with these storage elements, in a case where data of "0" or "1" is newly stored in a certain storage element, a state of change is induced by application of a predetermined voltage to the storage element or by allowing a current

20   to pass therethrough. At this time, the storage element is forced into a predetermined state by application of a predetermined voltage to the storage element or by allowing a current to pass therethrough, regardless of whether existing data that is previously stored in the

25   storage element is "0" or "1", thereby storing new data.

In a data storage device consisting of a semiconductor device including the conventional data storage circuit described above, however, new data is written by application of a voltage to the storage

30   element or by allowing a current to pass therethrough even though the previously stored existing data and the

new data to be written are identical. Therefore, there is a problem that substantially ineffective power consumption is generated ~~to~~ which hinder<u>a</u> power saving.

In particular, the storage element used for the

5   flash memory or the MRAM described above requires a considerable amount of electric power in view of its structure to cause a change of state in order to write new data. Therefore, wasteful power consumption is increased in the data storage circuit<u>,</u> such as the flash

10   memory or the MRAM<u>,</u> by the corresponding amount to further hinder power saving.

Disclosure of the Invention

Therefore, in order to solve the above problems, a

15   data storage circuit of the present invention is configured to have a comparison section for reading out existing data stored in a storage element to compare the existing data and new data with each other prior to writing of the new data to the storage element, and so

20   that, in the comparison section, if the exiting data and the new data are identical with each other, the writing to the storage element is not performed, and if the existing data and the new data are not identical with each other, the new data is written to the storage

25   element.

The data storage circuit is also characterized by including a control signal generating section for generating a readout control signal for performing readout control of the existing data and a write control

30   signal for performing write control of the new data, and being configured so that the existing data and the new

data are compared with each other in the comparison section in accordance with the control signal from the control signal generating section.

According to a data writing method in the data storage circuit of the present invention, it is arranged so that readout processing for reading out existing data stored in a predetermined storage element is performed prior to write processing of new data to the storage element so as to compare the exiting data and the new data with each other, and ~~that~~ if the existing data and the new data are identical with each other, the write processing to the storage element is not performed, and if the data not identical, the write processing of the new data to the storage element is performed.

Furthermore, the data writing method is also characterized by generating a readout control signal and a write control signal in accordance with a write signal input to the data storage circuit so as to read out the existing data in accordance with the readout control signal and to compare it with the new data in accordance with the write control signal.

In order to solve the above problems, a data storage device of the present invention is provided with a comparison section for reading out existing data stored in a storage element to compare the existing data and new data with each other prior to writing of the new data to the storage element, and the device is configured so that, in the comparison section, if the exiting data and the new data are identical with each other, the writing to the storage element is not performed, and if the existing data and the new data are not identical with each other,

4

the new data is written to the storage element.

Furthermore, the data storage device is also characterized by being provided with a control signal generating section for generating a readout control

5 signal for performing readout control of the existing data and a write control signal for performing write control of the new data, and in that the existing data and the new data are compared with each other in the comparison section in accordance with the control signal

10 from the control signal generating section.

Moreover, the data storage device is also characterized in that the comparison section thereof is provided with: a new data retention section for temporarily retaining the new data; an existing data

15 retention section for temporarily retaining the existing data; and a write enable signal generating section for comparing the new data retained in the new data retention section and the exiting data retained in the existing data retention section with each other to control an

20 output of the write enable signal, and ~~in that~~ the new data is temporarily retained in the new data retention section while the existing data is temporarily retained in the exiting data retention section in accordance with the readout control signal output from the control signal

25 generating section so as to compare the new data retained in the new data retention section and the existing data retained in the existing data retention section with each other in accordance with the write control signal output from the control signal generating section.

30

Brief Description of the Drawings

Fig. 1 is a block diagram showing a data storage circuit according to the present invention.

Fig. 2 is a circuit diagram explaining a configuration of a control signal generating section.

5   Fig. 3 is an explanatory view of a readout control signal and a write control signal generated at the control signal generation section.

Fig. 4 is a circuit diagram explaining a configuration of a comparison section.

10   Fig. 5 is a flow chart of a data writing process in the data storage circuit.

Best Mode for Carrying out the Invention

A data storage circuit and a data storage device

15   formed so as to include the data storage circuit according to the present invention respectively include a storage section consisting of a combination of a plurality of storage elements. If data is written to the data storage circuit and the data storage device,

20   existing data already stored in a predetermined storage element is read out in advance before new data is stored in the storage element so as to compare the existing data and the new data with each other. If they are identical with each other, the new data is not written; only if

25   ~~they~~ the dates are not identical with each other, the new data is written.

More specifically, in a case where it is not necessary to induce a change of state in the storage element because the existing data and the new data are

30   identical with each other, a voltage is not applied to the storage element or a current is not allowed to pass

therethrough. As a result, power consumption can be reduced by the corresponding amount to achieve a power saving.

In particular, since a probability that the

5   existing data and the new data will be identical with each other is about 50%, the power required to write the data to the storage element can be approximately halved, which greatly contributes to the power saving of the data storage circuit and the data storage device.

10   The data storage device is formed by providing the data storage circuit on a semiconductor substrate. In the following description, an explanation regarding the data storage circuit provided ing on the semiconductor substrate also serves as an explanation regarding the

15   data storage device.

However, the data storage circuit is not limited to those provided on the semiconductor substrate; it may be provided on an appropriate substrate other than the semiconductor substrate. Furthermore, the structural

20   form of the data storage device is not limited to that in which the data storage circuit is provided on a single semiconductor substrate; necessary circuits may be provided on a plurality of semiconductor substrates so as to be connected through an appropriate electric wiring.

25   eA comparison for determining if the exiting data and the new data are identical with each other or not is performed in the comparison section provided in the data storage circuit. After the existing data and the new data are fetched into the comparison section, comparison

30   processing is executed.

Furthermore, a control signal generating section

7

for detecting a write signal so as to generate a control signal described below is provided in the data storage circuit. The write signal is a so-called write enable signal. By detecting the write signal in the control

5 signal generating signal, the new data can be written to a predetermined storage element in accordance with a new data signal input from a new data input line connected to the data storage circuit.

In particular, the control signal generating
10 section generates a readout control signal for performing readout control of the existing data and a write control signal for performing write control of the new data as a result of the detection of the write signal.

Then, the control signal generating section first
15 outputs the readout control signal so as to read out the existing data in the predetermined storage element and to fetch it into the comparison section. Subsequently, the control signal generating section outputs the write control signal to compare the existing data and the new
20 data fetched into the comparison section with each other. If the existing data and the new data are not identical with each other, the comparison section outputs the write enable signal so as to execute writing of the new data to the storage element.

25 On the other hand, if the existing data and the new data are identical with each other, the comparison section does not output the write enable signal. Accordingly, the writing of new data to the storage element is not executed, so that wasteful power
30 consumption is suppressed.

An embodiment of the present invention will be

described in detail below with reference to the drawings.

Fig. 1 is a block diagram showing a data storage circuit 1 according to this embodiment. The data storage circuit 1 includes: a storage section 3 having a storage element area 2 in which a plurality of storage elements M are appropriately arranged; a control signal generating section 4 for detecting a write signal 6s that brings the storage section 3 into an input receiving state of new data; and a comparison section 5 for performing write control of the new data, which is stored in a predetermined one of the storage elements M of the storage section 3, to the storage element M in accordance with the detection of the write signal 6s.

Furthermore, to the data storage circuit 1, a new data input line 6 for inputting the new data to the storage section 3 is connected while a write signal line 7 for inputting a write signal 7s to the control signal generating section 4 is also connected.

In this embodiment, a ferromagnetic tunnel junction element is used as each of the storage elements M. The ferromagnetic tunnel junction elements are provided at the crossing points between a plurality of word lines 8 and bit lines 9 provided in a grid pattern in the storage element area 2. Although not shown, sense lines for reading-out are provided in parallel to the word lines 8 so as to read out data stored in the ferromagnetic tunnel junction elements.

Although the following description is given for a case where the storage element M is a ferromagnetic tunnel junction element, the storage element M is not limited to the ferromagnetic tunnel junction element. A

known storage element, such as an N-channel MOSFET
constituting a flash memory may also be used. In this
case, the word lines 8 and the bit lines 9 may be
appropriately provided in accordance with a writing mode
5   and a reading-out mode of the data to/from the storage
elements M.

Column drive control sections 10 are connected to
an end of each of the word lines 8 and an end of each of
the sense lines. Each of the column drive control
10 sections 10 is connected to a column decoder 11 so as to
operate in accordance with a control signal from the
column decoder 11. Moreover, a row drive control section
12 is connected to an end of each of the bit lines 9.
Each of the row drive control sections 12 is connected to
15 a row decoder 13 so as to operate in accordance with a
control signal from the row decoder 13.

A column address data output section 14 is
connected to the column decoder 11, whereas a row address
data output section 15 is connected to the row decoder 13.
20 An external input signal for specifying a predetermined
one of the storage elements M is configured to be input
from the column address data output section 14 to the
column decoder 11 as a column address data signal 14s and
to be input from the row address data output section 15
25 to the row address decoder 13 as a row address data
signal 15s.

Although it is depicted in Fig. 1 that the column
address data output section 14 and the row address data
output section 15 are provided outside of the data
30 storage circuit 1, the data storage circuit 1 may be
configured to include the column address data output

10

section 14 and the row address data output section 15.

The column decoder 11 performs decoding in accordance with the input column address data signal 14s so as to operate any one of the column drive control

5   sections 10 connected to the column decoder 11. The row decoder 13 performs decoding in accordance with the input row address data signal 15s so as to operate any one of the row drive control sections 12 connected to the row decoder 13. The storage element M, which is positioned

10 at a crossing point between the word line 8 or the sense line connected to the column drive control section 10 currently being operated and the bit line 9 connected to the row drive control section 12 similarly currently being operated, is brought into an operating state so as

15 to enable the write/readout of data to/from the storage element M.

In particular, in a case of writing new data to the storage element M or in a case of reading out existing data from the storage element M, the column address data

20 signal 14s output from the column address data output section 14 and the row address data signal 15s output from the row address data output section 15 bring the storage element M, to/from which writing or reading-out is performed, into an operating state in advance.

25 Furthermore, since the ferromagnetic tunnel junction element is used as the storage element M in this embodiment, the new data input lines 6 are connected to the row drive control sections 12, respectively. Then, the predetermined storage element M is brought into an

30 operating state as described above and a new data signal 6s is input to the row drive control section 12 through

the new data input line 6, so that the row drive control section 12 allows a current to pass through the bit line 9 in a predetermined direction, thereby writing the new data to the storage element M.

5 On the other hand, for reading out the existing data stored in the storage element M, the storage element M, from which reading-out is performed, is brought into an operating state as described above. A resistance value of the storage element M is detected by using the

10 sense line so as to generate an existing data signal in accordance with the resistance value detected in the column drive control section 10 and to output it to the column decoder 11.

The data storage circuit 1 is normally in a

15 protected state where a storage state in the storage element M is prevented from being automatically varied by an erroneous input of a noise and the like. By inputting the write signal 7s to the data storage circuit 1 as described above, the storage section 3 of the data

20 storage circuit 1 allows the input of the new data only when the write signal 7s is input to enable the writing of the new data.

In particular, with the detection of the write signal 7s, a readout control signal 16s and a write

25 control signal 17s are generated in the control signal generating section 4 for detecting the write signal 7s in the data storage circuit 1. The readout control signal 16s is a control signal for performing reading-out of the existing data from the storage element M to which the new

30 data is to be stored. The write control signal 17s is a control signal for performing writing of the new data to

the storage element M.

As shown in Fig. 2, a readout control signal generating section 18 and a write control signal generating section 19 are provided in parallel in the control signal generating section 4 so as to generate the readout control signal 16s and the write control signal 17s from the write signal 7s.

More specifically, in the control signal generating section 4, the write signal line 7 is branched into a readout control signal generating line 20 and a write control signal generating line 21 so as to input the write signal 7s to the readout control signal generating section 18 and the write control signal generating line 19, respectively. In this manner, the readout control signal 16s is generated in the readout control signal generating section 18, whereas the write control signal 17s is generated in the write control signal generating section 19.

In the readout control signal generating section 18, the readout control signal generating line 20 is further branched into a first readout control signal generating line 20a and a second readout control signal generating line 20b. The first readout control signal generating line 20a and the second readout control signal generating line 20b are connected to an AND gate 22 which generates the readout control signal 16s.

At this time, a NOT gate 23 is provided in the middle of the second readout control signal generating line 20b. Furthermore, a resistor 24 is provided on the output side of the NOT gate 23 to which an end of a capacitor 25 is connected. As a result, as shown in Fig.

3, the readout control signal generating section 18 detects a rise of the write signal 7s to generate the readout control signal 16s so as to output it from the readout control signal line 16 connected to the AND gate 22.

Moreover, in the write control signal generating section 19, the write control signal generating line 21 is also further branched into a first write control signal generating line 21a and a second write control signal generating line 21b. The first write control signal generating line 21a and the second write control signal generating line 21b are connected to a NOR gate 26 which generates the write control signal 17s.

At this time, a NOT gate 27 is provided in the middle of the second write control signal generating line 21b. Furthermore, a resistor 28 is provided on the output side of the NOT gate 27, to which an end of a capacitor 29 is connected. As a result, as shown in Fig. 3, the write control signal generating section 19 detects a fall of the write signal 17s to generate the write control signal 17s so as to output it from the write control signal line 17 connected to the NOR gate 26.

More specifically, since the readout control signal 16s and the write control signal 17s can be generated from the same write signal 7s, the readout control signal 16s and the write control signal 17s, which have a predetermined difference in time therebetween, can be generated with good accuracy with an extremely simple structure. Therefore, the control of the comparison section 5 described below by the readout control signal 16s and the write control signal 17s can be ensured.

As shown in Fig. 1, the readout control signal line 16 and the write control signal line 17 are connected to the column decoder 11 and the row decoder 13 so as to control the column decoder 11 and the row decoder 13 in

5 accordance with the readout control signal 16s and the write control signal 17s in a manner described below. Furthermore, the readout control signal line 16 and the write control signal line 17 are respectively connected to each of the column drive control sections 10 and each

10 of the row drive control sections 12 so as to control the column drive control sections 10 and the row drive control sections 12 in accordance with the readout control signal 16s and the write control signal 17s in a manner described below.

15 The readout control signal line 16 and the write control signal line 17 are also connected to the comparison section 5 so that the readout control signal 16s and the write control signal 17s are input to the comparison section 5 to control the comparison section 5.

20 Furthermore, the new data input line 6 and an existing data input line 30 ~~which~~ that is connected to the row decoder 11 are connected to the comparison section 5 so as to input thereto the new data signal 6s and an existing data signal 30s to be compared with each

25 other. ~~are input thereto.~~

As shown in Fig. 4, the comparison section 5 is configured with a new data signal retention section 31 for temporarily retaining the new data signal 6s input through the new data input line 6; an existing data

30 signal retention section 32 for temporarily retaining the existing data signal 30s input through the existing data

input line 30; and a write enable signal generating
section 33 for comparing the new data signal 6s retained
in the new data signal retention section 31 and the
existing data signal 30s retained in the existing data
5 signal retention section 32 with each other.

The new data signal retention section 31 is
configured with an input control transistor 34 for
controlling an input of the new data signal 6s to the new
data signal retention section 31; and a retention section
10 35 for retaining the new data signal 6s input to the new
data signal retention section 31.

The readout control signal line 16 is connected to
a gate electrode of the input control transistor 34. The
readout control signal 16s is input to the gate electrode
15 so that the new data signal 6s is input from the new data
input line 6 connected to the input control transistor 34
to the retention section 35 connected to the input
control transistor 34.

The retention section 35 is a simple storage
20 circuit consisting of a latch composed of the combination
of two inverters 36, which is capable of retaining the
new data signal 6s for a certain period of time.

Similarly to the new data signal retention section
31, the existing data signal retention section 32 is also
25 configured with an input control transistor 37 for
controlling an input of the existing data signal 30s to
the existing data signal retention section 32; and a
retention section 38 for retaining the existing data
signal 30s input to the existing data signal retention
30 section 32.

The readout control signal line 16 is connected to

a gate electrode of the input control transistor 37. The
readout control signal 16s is input to the gate electrode
so that the existing data signal 30s is input from the
existing data input line 30 connected to the input
5   control transistor 37 to the retention section 38
connected to the input control transistor 37.

The retention section 38 is a simple storage
circuit consisting of a latch composed of a combination
of two inverters 40, 40, which is capable of retaining
10 the existing data signal 30s for a certain period of time.

The write enable signal generating section 33 is
configured with an output control transistor 41 for
controlling an output of the new data signal 6s from the
new data signal retention section 31; an output control
15 transistor 42 for controlling an output of the existing
data signal 30s from the existing data signal retention
section 32; and an XOR gate 43 for inputting the new data
signal 6s and the existing data signal 30s output
respectively from the retention sections 35 and 38 by the
20 output control transistors 41 and 42 thereto.

In particular, the write control signal line 17 is
connected to gate electrodes of the output control
transistors 41 and 42, respectively. The write control
signal 17s is input to the output control transistors 41
25 and 42 through the write control signal line 17 so as to
output the new data signal 6s and the existing data
signal 30s from the retention sections 35 and 38 to the
XOR gate 43.

In a case where the input new data signal 6s and
30 the existing data signal 30s are not identical with each
other, the XOR gate 43 outputs the write enable signal

44s from the write enable signal line 44 connected to the XOR gate 43. In a case where the new data signal 6s and the existing data signal 30s are identical with each other, it does not output the write enable signal 44s.

It is possible to extremely easily compare the new data signal 6s and the existing data signal 30s by inputting the write control signal 17s to the gate signals of the output control transistors 41 and 42 and to simultaneously output the new data signal 6s and the existing data signal 30s from the new data signal retention section 31 and the existing data signal retention section 32. As a result, it is possible to simplify the structure of the write enable signal generating section 33.

Furthermore, since determination processing in the write enables signal generating section 33 can be performed within a short period of time, a processing speed can be improved.

Except for the time of inputting the write control signal 17s, an erroneous operation protect signal is input to the XOR gate 43 so as to prevent the XOR gate 43 from erroneously outputting the write enable signal 44s. In this embodiment, the control transistors 41, 42 and 45, each having the gate electrode to which the write control signal line 17 is connected, are used to control the erroneous operation protect signal.

As shown in Fig. 1, the write enable signal line 44 is configured so that it is connected to each of the column drive control sections 10 and each of the row drive control sections 12 so as to input the write enable signal 44s to each of the column drive control sections

10 and each of the row drive control sections 12.

Finally, in accordance with a flowchart of Fig. 5, an operation for storing the new data in the data storage circuit 1 configured as described above will be described.
5   When the new data is to be stored in the predetermined storage element M, the storage element M is brought into an operation state in advance as described above (step S1).

Then, to the data storage circuit 1, the new data
10   signal 6s is input from the new data input line 6 (step S2) while the write signal 7s is input from the write signal line 7 (step S3).

In accordance with the input of the write signal 7s, the control signal generating section 4 first outputs the
15   readout control signal 16s through the readout control signal line 16 (step S4) so as to input it to the column decoder 11, the row decoder 13, each of the column drive control sections 10, and each of the row drive control sections 12, thereby reading out the existing data stored
20   in the predetermined storage element M to the column decoder 11. The column decoder 11 outputs the readout existing data as the existing data signal 30s to the existing data input line 30 connected to the column decoder 11 (step S5). This corresponds to readout
25   processing.

The control signal generating section 4 also inputs the readout control signal 16s to the comparison section 5. In the comparison section 5, in response to the input of the readout control signal 16s, the new data signal 6s
30   is input to the new data signal retention section 31 of the comparison section 5 so as to be temporarily retained

19

therein, whereas the existing data signal 30s is input to the existing data signal retention section 32 so as to be temporarily retained therein (step S6).

After a predetermined period of time, the control signal generating section 4 generates the write control signal 17s in accordance with the write signal 7s so as to input the write control signal 17s to the comparison section 5 (step S7). The write control signal 17s regulates the write signal 7s so that it is output from the control signal generating section 4 after an elapse of a sufficient period of time to input the new data signal 6s and the existing data signal 30s to the comparison section 5 by the readout control signal 16s.

The comparison section 5 outputs and compares the new data signal 6s retained in the new data signal retention section 31 and the exiting data signal 30s retained in the existing data signal retention section 32 in accordance with the input write control signal 17s (step S8).

In a case where the new data signal 6s and the existing data signal 30s are not identical with each other, it means the new data and the existing data are different from each other. Therefore, the comparison section 5 outputs the write enable signal 44s (step S9).

At this time, the write control signal 17s output from the control signal generating section 4 is also input to the column decoder 11, the row decoder 13, each of the column drive control sections 10 and each of the row drive control sections 12 through the write control signal line 17. Furthermore, the write enable signal 44s output from the comparison section 5 is input to each of

the column drive control sections 10 and each of the row drive control sections 12 through the write enables signal line 44, so that the storage section 3 writes the new data to the predetermined storage element M (step

5   S10). This corresponds to write processing.

On the other hand, in the comparison between the new data signal 6s and the existing data signal 30s in the comparison section 5 (step S8), in a case where the new data signal 6s and the exiting data signal 30s are

10   identical with each other, that is, in a case where the new data and the existing data are identical with each other, the comparison section 5 does not output the write enable signal 44s. The write processing is terminated while the storage section 3 does not write the new data

15   to the predetermined storage element M.

Since the existing data already stored in the storage element M is the same as the new data even if the new data is not written to the storage element M, ~~there arises~~ no problem _arises_.

20   As described above, in a case where the new data to be stored in the storage element M is identical with the existing data already stored in the storage element M to which the new data is to be written, the new data is not written. As a result, the power consumption, which would

25   otherwise be generated by writing the new data, can be reduced, thereby achieving _a_ power saving.

By providing the above-described data storage circuit 1 on a semiconductor substrate, a data storage device achieving _a_ power reduction can be formed. By

30   using the data storage device, a CPU including an IC memory or a storage area with _a_ power reduction can be

formed.

Industrial Applicability

(1) In the present invention as described in Claim
1, by providing a comparison section for reading out
existing data stored in a storage element to compare the
existing data and new data with each other prior to
writing of the new data to the storage element, and
configuring so that, in the comparison section, in a case
where the exiting data and the new data are identical
with each other, the writing to the storage element is
not performed, and in a case where the existing data and
the new data are not identical with each other, the new
data is written to the storage element, it is possible to
substantially reduce the number of times of execution of
writing to the storage element so that power consumption
brought by the writing of the new data can be suppressed
to accomplish power saving.

In particular, since a probability that the
existing data and the new data will be identical with
each other is about 50%, the power required to write the
data to the storage element can be approximately halved.

(2) According to the invention as described in
Claim 2, by providing the data storage circuit with a
control signal generating section for generating a
readout control signal for performing readout control of
the existing data and a write control signal for
performing write control of the new data, and by
configuring the data storage circuit so that the existing
data and the new data are compared with each other in the
comparison section in accordance with the control signal

from the control signal generating section, the readout

control signal and the write control signal generated

with good accuracy can surely perform control of the data

storage circuit and avoid erroneous operation to prevent

5   excess power consumption. In particular, it is possible

to adjust a time difference between the readout control

signal and the write control signal generated with a

predetermined time difference therebetween to be minimal

so that the processing at the comparison section can be

10   performed at high speed.

(3) According to the invention as described in

Claim 3, by performing a readout process of existing data

stored in a storage element prior to performing a write

process of the new data to the storage element to compare

15   the existing data and the new data with each other so as

not to perform the writing to the storage element in a

case where the exiting data and the new data are

identical with each other and so as to perform writing of

the new data to the storage element in a case where the

20   existing data and the new data are not identical with

each other, similarly to the invention as described in

Claim 1, it is possible to substantially reduce the

number of times of execution of writing to the storage

element so that power consumption brought by the writing

25   of the new data can be suppressed to accomplish a power

saving ~~since~~ because the writing is not performed in a

case of the existing data and the new data being

identical to each other.

(4) According to the invention as described in

30   Claim 4, by generating a readout control signal and a

write control signal in accordance with a write signal

input to the data storage circuit and by reading out the existing data in accordance with the readout control signal to compare the existing data with the new data in accordance with the write control signal, it is possible

5   to perform the write processing of the new data immediately subsequent to the readout processing of the existing data so that a processing speed can be improved and erroneous operation is avoided to prevent excess power consumption.

10   (5) According to the invention as described in Claim 5, by providing a comparison section for reading out existing data stored in a storage element to compare the existing data and new data with each other prior to writing of the new data to the storage element, and

15   configuring so that, in the comparison section, in a case where the exiting data and the new data are identical with each other, the writing to the storage element is not performed, and in a case where the existing data and the new data are not identical with each other, the new

20   data is written to the storage element, similarly to the invention as described in Claim 1, it is possible to substantially reduce the number of times of execution of writing to the storage element so that power consumption brought by the writing of the new data can be suppressed

25   to accomplish a power saving.

          (6) According to the invention as described in Claim 6, by providing the data storage device with a control signal generating section for generating a readout control signal for performing readout control of

30   the existing data and a write control signal for performing write control of the new data, and by

configuring the data storage circuit so that the existing data and the new data are compared with each other in the comparison section in accordance with the control signal from the control signal generating section, similarly to

5   the invention as described in Claim 2, the readout control signal and the write control signal generated with good accuracy can surely perform control of the data storage circuit and avoid erroneous operation to prevent excess power consumption. In particular, it is possible

10 to adjust a time difference between the readout control signal and the write control signal generated with a predetermined time difference therebetween to be minimal so that the processing at the comparison section can be performed at a high speed.

15   (7) According to the invention as described in Claim 7, by providing the comparison section with a new data retention section for temporarily retaining the new data; an existing data retention section for temporarily retaining the existing data; and a write enable signal

20 generating section for comparing the new data retained in the new data retention section and the exiting data retained in the existing data retention section with each other to control an output of the write enable signal, and configuring so that the new data is temporarily

25 retained in the new data retention section while the existing data is temporarily retained in the exiting data retention section in accordance with the readout control signal output from the control signal generating section so as to compare the new data retained in the new data

30 retention section and the existing data retained in the existing data retention section with each other in

accordance with the write control signal output from the control signal generating section, it is possible to compare the new data and the existing data after correctly obtaining them, respectively, so as to avoid <u>an</u> erroneous operation so that excessive power consumption can be prevented.